



NOTES:

SPECIFICATION:

1. CURRENT RATING: 3.0A MAX
2. DIELECTRIC WITHSTAND VOLTAGE: 100VAC
3. TEMPERATURE RANGE: -30 °C ~ 85 °C
4. CONTACT RESISTANCE: 40 MILLIONHM MAX
5. INSULATION RESISTANCE: 100 MEGOHMS MIN.
6. INSERTION FORCE : 5N~20N
7. UNMATING FORCE: 8N~20N
8. DURABILITY:5000 CYCLES

A5	CC1	B12	GND
A9	VBUS	B9	VBUS
A12	GND	B5	CC2
PIN	SIGNAL NAME	PIN	SIGNAL NAME

4	Shell1	1	SUS301 Ni Plating T=0.25mm	Ni:40~120u"
3	Housing2	1	LCP(G.F30%)	
2	Contact	5	Phosphor bronze C5210R-EH Au/Ni Plating T=0.20mm	Ni:40~160u" Au:CONTACT AREA:3u" OTHER AREA:G/F
1	Housing	1	PA9T (G.F30%)	
ITEM	PART NAME	Q' TY	FINISH	NOTE

一般公差 GENERAL TOLERANCE	
X.X ±0.30	X' ±2'
X.XX ±0.20	X.X' ±1'
X.XXX ±0.10	▲ MAJOR DIM.
单位 UNIT	
mm	

绘图 DR.	李兴泽
校对 CHK.	
审核 CHK.	
核准 APPD.	

料号 PART NO.	文件编号 NUMBER
W-UTP-6P-FS24	ENDPT01
品名 TITLE	
USB TYPE C 6 PIN 防水	

<b>JCTC</b> ®		
TERMINAL&CONNECTORS		
比例 SCALE	SHEET	版次 REV.
1/1	1/1	A0

A0	19.11.15	新图面发行	李兴泽		
版次 REV.	日期 DATE	变更内容 DESCRIPTION	审核 CHK.	核准 APPD.	