



Circuits	Dimensions		
	A	B	C
2P	2.50	4.50	3.20
3P	3.75	5.75	4.45
4P	5.00	7.00	5.70
5P	6.25	8.25	6.95
6P	7.50	9.50	8.20
7P	8.75	10.75	9.45
8P	10.00	12.00	10.70
9P	11.25	13.25	11.95
10P	12.50	14.50	13.20
11P	13.75	15.75	14.45
12P	15.00	17.00	15.70
13P	16.25	18.25	16.95
14P	17.50	19.50	18.20
15P	18.75	20.75	19.45
16P	20.00	22.00	20.70

Specifications:
 Rated Voltage : 50V AC/DC
 Rated Current : 2.2A AC/DC
 Withstand Voltage : 500V AC/minute
 Contact Resistance : 20mΩ(MAX.)
 Insulation Resistance : 100MΩ(MIN.)
 Temperature Range : -25°C~+85°C
 Dry state : Pressing the lock is not allow
 The product using material and processing must conform to the "WI-PZ-142" HSF technical standard control requirements

Part No.	Material	Color
11254H00-NP-L-HF	Nylon 66,UL 94V-0	Natural(White)
11254H00-NPA-L-HF	Nylon 66,UL 94V-0	Black

REV.	REVISION RECORD	DATE		GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	PART. NO: 11254H00-NP-L-XX	DWG. NO: ENDE05	 TERMINAL&CONNECTORS
A0	新版发行	21.04.19		LINEAR	ANGLES	APPROVED	Nelson	23.02.11			
			UNIT: MM	0.00±0.15	X° ±3°	DESIGNER	VM	23.02.11	TITLE: Molex 1.25 HSG	REV: A0	
			SIZE: A4	0.000±0.08	X° X' ±2°	DRAWN	Fau	23.02.11			