



Specifications:
 Voltage Rating : 50V AC/DC
 Current Rating : 1A AC,DC
 Withstand Voltage : 500V AC/minute
 Contact Resistance : 20mΩ (MAX.)
 Insulation Resistance : 500MΩ (MIN.)
 Temperature Range : -25° C ~ +85° C

The product using material and processing must conform to the "WI-PZ-142-HSF" technical standard control requirements

11501W90-NPX-H1-HF
 ① ② ③ ④ ⑤ ⑥

- ① Series No.
- ② W90 : Side Contact
W00 : Up Contact
- ③ No. of Circuits
- ④ X : Product color (A-Y)
Blank : Natural type
- ⑤ H1 : Nylon 6T
- ⑥ HF : Halogen Free



Dimensional Ordering Information:				
Circuits	Dimensions			
	Part No	A	B	C
2P	1.50	3.70	4.50	
3P	3.00	5.20	6.00	
4P	4.50	6.70	7.50	
5P	6.00	8.20	9.00	
6P	7.50	9.70	10.50	
7P	9.00	11.20	12.00	
8P	10.50	12.70	13.50	
9P	12.00	14.20	15.00	
10P	13.50	15.70	16.50	
11P	15.00	17.20	18.00	
12P	16.50	18.70	19.50	
13P	18.00	20.20	21.00	
14P	19.50	21.70	22.50	
15P	21.00	23.20	24.00	

Part No.	Material	Color	Pin Material
11501W90-NP	Nylon 66, UL 94V-0	本色	Brass/Tin-plated
11501W90-NPJ	Nylon 66, UL 94V-0	灰色	Brass/Tin-plated
11501W90-NP-6T	Nylon 6T, UL 94V-0	本色	Brass/Tin-plated
11501W90-NP-H1-HF	Nylon 10T, UL 94V-0	本色/无卤	Brass/Tin-plated



REV.	REVISION RECORD	DATE	GENERAL TOLERANCES	SCALE 1:1	NAME	DATE	PART NO.	DWG NO.	TITLE			
C1	HN1109130131	11.09.13	LINEAR	APPROVED	Nelson	23.01.12	11501W90-NPX	ENDE05	ZH 1.50mm PITCH CONN			
C2	WN1611030179	16.11.07	ANGLES	DESIGNER	VM	23.01.12						
C3	依PBJOA202207190005新增	22.12.29	0.00±0.15	DRAWN	HZJ	23.01.12						
C4	依ECN20230112355变更材料	23.01.12	0.000±0.08									
			UNIT: MM						REV	C4	SHEET	1/1

