


12001W00-NPX-S1-XX-HF

① ② ③ ④ ⑤ ⑥ ⑦

- ① Series No.
- ② W90 : Side Contact
W00 : Up Contact
- ③ No. of Circuits
- ④ X : Product color(A--Y)
- ⑤ S1 : S1 Type
- ⑥ XX : 5A--Gold flash 5B--2u" 5C--3u"
5D--4u" 5E--5u" 5F--10u"
5G--15u" 5H--30u"
- ⑦ HF : Halogen Free



PART NO.	Dimensions	
	A	B
2P	--	6.00
3P	4.00	8.00
4P	6.00	10.00
5P	8.00	12.00
6P	10.00	14.00
7P	12.00	16.00
8P	14.00	18.00
9P	16.00	20.00
10P	18.00	22.00
11P	20.00	24.00
12P	22.00	26.00
13P	24.00	28.00
14P	26.00	30.00
15P	28.00	32.00
16P	30.00	34.00

Specifications:
 Rated Voltage : 100V AC/DC
 Rated Current : 3A AC,DC
 Withstand Voltage : 800V AC/minute
 Contact Resistance : 10mΩ(MAX.)
 Insulation Resistance : 1000MΩ(MIN.)
 Temperature Range : -25°C~+85°C
 The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements

Part No.	Material	Color	PIN Material
12001W00-NP-S1-5A-HF	HTN,UL94V-0	Natural(Beige)	Barss/Au 1u"
12001W00-NP-S1-5G-HF	HTN,UL94V-0	Natural(Beige)	Barss/Au 15u"
12001W00-NP-S1-HF	HTN,UL94V-0	Natural(Beige)	Barss/Tin-plated
12001W00-NPA-S1-HF	HTN,UL94V-0	Black	Barss/Tin-plated

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES	SCALE	NAME	DATE	PART NO.	DWG NO.	JCTC® TERMINAL&CONNECTORS			
A0	新版发行	2018.09.20	LINEAR	1:1	Nelson YZY	23.05.25 2023.05.25	12001W00-NPX-S1-HF	ENDE05				
A1	增加黑色规格	2019.05.30	ANGLES	APPROVED								
A2	增加镀金规格料号	2022.01.10	0.00±0.25 X° REF±6°	DESIGNER								
A3	依PB,JOA202202110006新增	2023.05.25	0.00±0.15 X° ±3°	0.00±0.08 X° X'±2°	DRAWN	HZX	2023.05.25	TITLE	2.00mm PITCH DIP TYPE 180° WAFER			
			UNIT: MM						REV	A3	SHEET	1/1