



12504W00-NPX-L-XX-HF

- ① Series No.
- ② W90 : Side Contact
W00 : Up Contact
- ③ No. of Circuits
- ④ X : Product color(A--Y)
Blank: Natural type
B: Blue; C: Red;
E: Yellow; F: Green
- ⑤ L: Lock TYPE
- ⑥ Blank: Tin-plated
SA: Gold Flash
- ⑦ HF : Halogen Free

Specifications:
 Rated Voltage : 250V AC/DC
 Rated Current : 3A AC,DC
 Withstand Voltage :1000V AC/minute
 Contact Resistance : 30mΩ(MAX.)
 Insulation Resistance : 1000MΩ(MIN.)
 Temperature Range : -25°C~+85°C
 Contact: Brass/Tin or Au
 Material: Nylon 66,UL94V-0, Halogen Free
 The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements

Circuits	Dimensions		
	A	B	C
2P	--	7.50	5.80
3P	5.00	10.00	8.30
4P	7.50	12.50	10.80
5P	10.00	15.00	13.30
6P	12.50	17.50	15.80
7P	15.00	20.00	18.30
8P	17.50	22.50	20.80
9P	20.00	25.00	23.30
10P	22.50	27.50	25.80
11P	25.00	30.00	28.30
12P	27.50	32.50	30.80
13P	30.00	35.00	33.30
14P	32.50	37.50	35.80
15P	35.00	40.00	38.30

REV.	REVISION RECORD	DATE	GENERAL TOLERANCES	SCALE	NAME	DATE	PART NO.	DWG NO.
C2	依开发单1812100257	18.12.13	LINER	1:1	赵稳	23.10.31	12504W00-NP-L-HF	ENDE05
C3	依YB20230130001新增规格	23.02.07	ANGLES	APPROVED	赵稳	2023.10.31		
C4	依YB202307200003新增规格	2023.10.31	0.0±0.25 X° REF±6°	DESIGNER	赵稳	2023.10.31		
			0.00±0.15 X° ±3°	DRAWN	YGT	2023.10.31		
			0.000±0.08 X° X' ±2°				TITLE	
							2.50mm PITCH DIP TYPE 180° WAFER	
								REV C4 SHEET 1/1

