


Specifications:
 Voltage Rating : 250V AC/DC
 Current Rating : 3A AC, DC
 Withstand Voltage : 1000V AC/minute
 Contact Resistance : 10mΩ (MAX.)
 Insulation Resistance : 1000MΩ (MTN.)
 Temperature Range : -25° C ~ +85° C
 The product using material and processing must conform to the "WI-PZ-142"HSF technical standard control requirements

Circuits Part No	Dimensions	
	A	B
2P	—	7.50
3P	5.00	10.00
4P	7.50	12.50
5P	10.00	15.00
6P	12.50	17.50
7P	15.00	20.00
8P	17.50	22.50
9P	20.00	25.00
10P	22.50	27.50
11P	25.00	30.00
12P	27.50	32.50
13P	30.00	35.00
14P	32.50	37.50
15P	35.00	40.00

Part No.	Insulator	Contact	Notes
12505W00-NP-H1	Nylon 9T, UL94V-0/Nature	Brass/Tin-plated	Without Boss Halogen Free
12505W00-NP-HF	Nylon 66, UL94V-0/Nature	Brass/Tin-plated	
12505W00-NPA-HF	Nylon 66, UL94V-0/Black	Brass/Tin-plated	With Boss Halogen Free
12505W00-NP-F-HF	Nylon 66, UL94V-0/Nature	Brass/Tin-plated	
12505W00-NP-F-5A-HF	Nylon 66, UL94V-0/Nature	Brass/Gold Falsh	
12505W00-NP-F-H1	Nylon 9T, UL94V-0/Nature	Brass/Tin-plated	
12505W00-NP-F-H1-5G	Nylon 9T, UL94V-0/Nature	Brass/15u"Gold	
12505W00-NPC-F-H1-5G	Nylon 10T, UL94V-0/Red	Brass/15u"Gold	
12505W00-NPC-F-HF	Nylon 66, UL94V-0/Red	Brass/Tin-plated	
12505W00-NPE-F-HF	Nylon 66, UL94V-0/Yellow	Brass/Tin-plated	
12505W00-NPG-F-HF	Nylon 66, UL94V-0/Blue	Brass/Tin-plated	

- 12505W00-NP-F-XX-5G
 ① ② ③ ④ ⑤ ⑥
 ① Series No.
 ② W90 : Side Contact
 W00 : Up Contact
 ③ No. of Circuits
 ④ F : With Boss
 ⑤ HF : HF Type
 H1 : H1 Type
 ⑥ 5G : 15u"Gold Type



REV.	REVISION RECORD	DATE
A0	The new version file were released	2014.12.12
A2	PBJ0A202207140002	2022.07.21
A3	YB202405150002	2024.05.31
A4	YB202411040006	2024.11.15

GENERAL TOLERANCES	SCALE 1:1	NAME	DATE
	LINEAR		
0.0 ± 0.25	X° REF ± 6°	J	24.11.25
0.00 ± 0.15	X° ± 3°	M	24.11.25
0.000 ± 0.08	X° X' ± 2°	WDH	24.11.15

PART NO.	DWG NO.
12505W00-NP-HF	ENDE05

TITLE			
2.50mm PITCH DIP TYPE WAFER			
REV	A4	SHEET	1/1

