



P.C.B Layout  
General tolerances: ±0.05mm

12540W90-4PA-F-B-HF

- ① Series No.
- ② W90 : Side Contact  
W00 : Up Contact
- ③ No. of Circuits
- ④ A: Black
- ⑤ F: With Post
- ⑥ B: B Type
- ⑦ HF: Halogen Free

Specifications:  
 Rated Voltage: 50V AC/DC  
 Rated Current: 7.5A AC,DC (AWG 18#)  
 Withstand Voltage: 1000V AC/minute  
 Contact Resistance: 30mΩ(MAX.)  
 Insulation Resistance: 1000MΩ(MIN.)  
 Temperature Range: -40°C~+105°C  
 The product using material and processing must conform to the "WI-PZ-142" HSF technical standard control requirements



Part No.	Insulator	Color	Contact
12540W90-NPA-F-B-HF	Nylon 66+25%GF,UL94V-0	Black	Copper alloy/Matte tin-plated

REV.	REVISION RECORD	DATE
A0	新版发行	21.06.10

GENERAL TOLERANCES	
LINEAR	ANGLES
0.0±0.25	X° REF±6°
0.00±0.15	X° ±3°
0.000±0.08	X° X'±2°

SCALE: 1:1	NAME: Nelson	DATE: 21.06.10
APPROVED:		
DESIGNER: 伍文聪	DATE: 21.06.10	
DRAWN: 伍文聪	DATE: 21.06.10	

PART. NO: 12540W90-NPX-F-B-HF	DWG. NO: ENDE05
TITLE: TE 2.54mm Pitch Wafer DIP 90° (卡板型)	

<b>JCTC</b> ®	
TERMINAL&CONNECTORS	
REV: A0	SHEET: 1/1